

Surface Grip Footprints

Product Parts

- 1 - Left Surface Grip Footprint (x5)
- 2 - Right Surface Grip Footprint (x5)



Display Set-Up

DO NOT FOLD YOUR INDOOR SURFACE GRIP

Step 1

Surface Preparation:

Prior to application, remove loose dirt or particles from application surface. Extremely dirty surfaces may require washing before application, but the surface must be completely dry before the graphic is applied.

Recommended minimum surface application temperature is 50° F.

Service temperature range is 20° F to 150° F.

Step 2

Peel a small strip of liner from the back side of graphic and crease the liner. Be careful not to touch the adhesive.

Orient the graphic, gently apply the exposed adhesive surface, and slowly continue to apply the graphic, removing the liner as you are applying. Do not remove the entire liner before applying, as this may cause excessive air bubbles.

Use a soft rubber roller or squeegee on the surface of the graphic to remove any air bubbles, and make sure it's fully adhered to the surface.

Surface Grip is REPOSITIONABLE and will work on walls, and flooring.

Step 3

*Removal:

To remove the graphic, simply lift one corner and continue to pull back slowly.

* When removed it will not leave adhesive residue.

Storage & Care

DO NOT FOLD YOUR INDOOR SURFACE GRIP

Store in a cool, dry place. Scuff marks or dirt can be removed with a mild detergent and a clean, damp cloth.